

WS-8-150-AC
Marks Switch 1Total Throughput
4/29/2019 3:00:18 PM

430.33	430.69
<small>TX Mbps</small>	<small>RX Mbps</small>
55.62	55.46
<small>TX Kpps</small>	<small>RX Kpps</small>

Total 0W 150W

Status Ports VLANs LAG STP QoS Tools ▾ ERPS Power Device ▾

Utilities ▾

Save/Apply

Configuration

Switch

Name	<input type="text" value="Marks Switch 1"/>
Location	<input type="text" value="Location"/>
Revert Timer	<input type="text" value="300"/>

GPS

Latitude	<input type="text" value="Latitude"/>
Longitude	<input type="text" value="Longitude"/>

NTP

Enable ☒

Host	<input type="text" value="129.6.15.28"/>
Zone	<input type="text" value="America/North Dakota/C ▾"/>

IPv4

Mode	<input type="text" value="Static ▾"/>
Address	<input type="text" value="10.10.150.151"/>
Netmask	<input type="text" value="255.255.255.0"/>
Gateway	<input type="text" value="10.10.150.1"/>
Primary DNS	<input type="text" value="8.8.8.8"/>
Secondary DNS	<input type="text" value="Secondary DNS"/>

IPv6

Enable ☐

Mode	<input type="text" value="DHCP ▾"/>
Address	<input type="text" value="Address"/>
Gateway	<input type="text" value="Gateway"/>
Primary DNS	<input type="text" value="Primary DNS"/>
Secondary DNS	<input type="text" value="Secondary DNS"/>

SMTP

☐ Test Enable ☒

Host	<input type="text" value="mail.vicihorizon.com"/>
Port	<input type="text" value="25"/>
Username	<input type="text" value="shop@vicihorizon.com"/>
Password	<input type="text" value="....."/>
Secure	<input type="checkbox"/>
Address	<input type="text" value="shop@vicihorizon.com"/>
From Address	<input type="text" value="shop@vicihorizon.com"/>
Local Hostname	<input type="text" value="Local Hostname"/>

SSH

Enable ☒

Port	<input type="text" value="22"/>
Allow Passwords	<input checked="" type="checkbox"/> <input type="button" value="Keys..."/>
Allow Telnet	<input type="checkbox"/>

HTTPS

Enable ☒

Port	<input type="text" value="443"/>
Allow HTTP	<input type="checkbox"/>
HTTP Port	<input type="text" value="80"/>

Syslog

Enable ☐

Host	<input type="text" value="Host"/>
Port	<input type="text" value="514"/>
Buffer Size	<input type="text" value="128"/>
NMS IP	<input type="text" value="NMS IP"/>
Log Logins	<input type="checkbox"/>

Storm Control

Broadcast	<input type="text" value="1024K ▾"/>
Multicast	<input type="text" value="1024K ▾"/>
Unicast	<input type="text" value="1024K ▾"/>
Pause Frame	<input checked="" type="checkbox"/>
Loop Protection	<input type="checkbox"/>

SNMP Server

Enable ☐

Contact	<input type="text" value="Contact"/>
Location	<input type="text" value="Location"/>
Community	<input type="text" value="public"/>
Version 1	<input type="checkbox"/>
Version 2c	<input type="checkbox"/>

Credentials

Name	<input type="text" value="admin"/>
Password	<input type="text" value="Password"/>
Confirm	<input type="text" value="Confirm"/>
Console Login	<input type="checkbox"/>

Discovery

Ubiquiti	<input checked="" type="checkbox"/>
Cisco	<input type="checkbox"/>
LLDP	<input type="checkbox"/>
Discovery Tab	<input type="checkbox"/>

Auto Backup

Enable ☐

TFTP URL	<input type="text" value="TFTP URL"/>
----------	---------------------------------------

RADIUS

Enable ☐

Host	<input type="text" value="Host"/>
Port	<input type="text" value="1812"/>
Secret	<input type="text" value="Secret"/>

Options

IGMP Snooping	<input type="checkbox"/>
Language	<input type="text" value="English ▾"/>
MAC Aging	<input type="text" value="300"/>

Serial Proxy ⓘ

Mode	<input type="text" value="Console ▾"/>
------	--